

Average Face Velocity*		300	400	500	600	700
10 x 6	CFM	115	150	190	225	265
Ak .38	Pt	.013	.023	.037	.052	.072
12 x 6	CFM	135	180	230	280	320
Ak .46	Pt	.013	.022	.035	.051	.070
10 x 8	CFM	150	205	255	305	355
Ak .51	Pt	.012	.022	.035	.050	.068
14 x 6	CFM	160	210	265	320	370
Ak .53	Pt	.012	.022	.035	.050	.068
12 x 8	CFM	180	245	305	365	430
Ak .61	Pt	.012	.022	.034	.049	.066
14 x 8	CFM	215	288	360	430	505
Ak .72	Pt	.012	.021	.033	.047	.065
20 x 6	CFM	225	300	375	450	525
Ak .75	Pt	.012	.021	.033	.047	.064
16 x 8	CFM	250	330	415	500	580
Ak .83	Pt	.012	.021	.033	.046	.063
14 x 10 and	CFM	275	365	460	550	640
Ak .92	Pt	.011	.020	.032	.045	.062
14 x 12	CFM	320	430	540	650	755
Ak 1.08	Pt	.011	.020	.031	.045	.060
30 x 6	CFM	335	445	560	670	780
Ak 1.12	Pt	.011	.020	.031	.044	.060
24 x 8	CFM	365	485	605	730	850
Ak 1.21	Pt	.011	.020	.031	.044	.059
20 x 10	CFM	375	500	630	750	880
Ak 1.25	Pt	.011	.019	.030	.043	.059
24 x 10 and	CFM	450	600	750	890	1040
Ak 1.50	Pt	.011	.019	.030	.042	.057
24 x 12	CFM	550	730	910	1100	1270
Ak 1.82	Pt	.010	.018	.029	.041	.056
30 x 10	CFM	575	760	960	1150	1330
Ak 1.91	Pt	.010	.018	.029	.041	.055
30 x 12	CFM	680	900	1130	1350	1570
Ak 2.25	Pt	.010	.018	.028	.040	.054

*Velocity measured 1" from face